



DATA SHEET

FINE WHITE POLYESTER MASTIC PLASTOBOAT

Fine polyester repair mastic for laminate boats. It is recommended for finishing and can be used on **FIBROBOAT**.

Its use is not recommended on immersed parts.

It can be used to level off areas after repair, and is resistant to impact and temperatures between -30°C and +125°C.

PHYSICAL CHARACTERISTICS

Colour : White
Odour : Styrene
Specific weight : 1.92
Flash point in closed vessel : 23°C ≤ PE ≤ 55°C
Self-igniting temperature : -
Resistance to temperature : -30 to +120°C
Chemical reaction : Exothermal reaction

PREPARATION OF THE SURFACE

The surface must be clean and dry. Remove all traces of grease and dust in order to get perfect adhesion.

APPLICATION

Mix the mastic well with 2% of catalyser, and apply within no more than 5 minutes.

After drying (about 30 minutes at 20°C), the product can be sanded and filed.

Close the container well after use, and keep it cool.

PACKING AND STORAGE

Packaging : 250 g, 500 g and 1.8 kg
Storage: Store in a cool, dry place.

PRECAUTIONS FOR USE

Keep out of reach of children. Ensure that the room is well ventilated.

HEALTH AND SAFETY

See data sheet

*This information corresponds to the actual state of our knowledge and has the sole object of informing you about our products and possible applications. It is objectively given but does not imply any guarantee by us.
Our company may modify all these details at any time*